

Fysetc R4

Original Image

```
[Dec11 21:15] usb 1-1.2: new full-speed USB device number 19 using xhci_hcd
[ +0.118169] usb 1-1.2: New USB device found, idVendor=2e8a,
idProduct=f00a, bcdDevice= 1.00
[ +0.000025] usb 1-1.2: New USB device strings: Mfr=1, Product=2,
SerialNumber=3
[ +0.000013] usb 1-1.2: Product: PicoArduino
[ +0.000011] usb 1-1.2: Manufacturer: Raspberry Pi
[ +0.000009] usb 1-1.2: SerialNumber: E661AC8863275126
[ +0.017217] cdc_acm 1-1.2:1.0: ttyACM1: USB ACM device
```

Klipper

- [*] Enable extra low-level configuration options
Micro-controller Architecture (Raspberry Pi RP2040/RP235x) --->
Processor model (rp2040) --->
Bootloader offset (No bootloader) --->
Flash chip (W25Q080 with CLKDIV 2) --->
Communication Interface (USBSERIAL) --->
USB ids --->
() GPIO pins to set at micro-controller startup
- make flash FLASH_DEVICE=2e8a:0003

From:

<https://www.drklipper.de/> - Dr. Klipper Wiki

Permanent link:

https://www.drklipper.de/doku.php?id=klipper_faq:flash_guide:rp2040:fysetc_r4&rev=1733948359

Last update: **2024/12/11 21:19**

