

# Fysetc Catalyst Bullant

## Übersicht

Catalyst	Bullant
<b>Repo</b> <a href="https://github.com/FYSETC/Catalyst_Kit_V2.0">https://github.com/FYSETC/Catalyst_Kit_V2.0</a>	<a href="https://github.com/FYSETC/FYSETC_Bullant_V1.0">https://github.com/FYSETC/FYSETC_Bullant_V1.0</a>
<b>Image</b> <a href="https://github.com/FYSETC/Catalyst_Kit_V2.0/blob/449f84ea78f707c273e316bcebbfd13e400e57/software/update_voron0_2_20240108.rar">https://github.com/FYSETC/Catalyst_Kit_V2.0/blob/449f84ea78f707c273e316bcebbfd13e400e57/software/update_voron0_2_20240108.rar</a> <a href="https://github.com/FYSETC/FYSETC-Voron-0.2-Pro/tree/main/0.2%20R1%20V1.1">https://github.com/FYSETC/FYSETC-Voron-0.2-Pro/tree/main/0.2%20R1%20V1.1</a>	<a href="https://github.com/FYSETC/FYSETC_Bullant_V1.0/blob/90d78536b823cc0e31b075f60f8d90145677ea5/software/Bullant_Armbian_OS_Klipper_Build_in_V1.0.rar">https://github.com/FYSETC/FYSETC_Bullant_V1.0/blob/90d78536b823cc0e31b075f60f8d90145677ea5/software/Bullant_Armbian_OS_Klipper_Build_in_V1.0.rar</a>
<b>User / Passwort</b> Default: linaro/linaro, root/root	Default: bullant/armbian, root/armbian
<b>Hostname</b> maixsense	maixsense
<b>Schaltplan</b> <a href="https://github.com/FYSETC/Catalyst_Kit_V2.0/blob/449f84ea78f707c273e316bcebbfd13e400e57/hardware/CATALYST%20V2.0%20SCH.pdf">https://github.com/FYSETC/Catalyst_Kit_V2.0/blob/449f84ea78f707c273e316bcebbfd13e400e57/hardware/CATALYST%20V2.0%20SCH.pdf</a>	<a href="https://github.com/FYSETC/FYSETC_Bullant_V1.0/blob/90d78536b823cc0e31b075f60f8d90145677ea5/Bullant%20V1.0%20SCH.pdf">https://github.com/FYSETC/FYSETC_Bullant_V1.0/blob/90d78536b823cc0e31b075f60f8d90145677ea5/Bullant%20V1.0%20SCH.pdf</a>
<b>Pinout</b> <a href="https://github.com/FYSETC/Catalyst_Kit_V2.0/blob/449f84ea78f707c273e316bcebbfd13e400e57/hardware/CATALYST%20V2.0%20Pinout.png">https://github.com/FYSETC/Catalyst_Kit_V2.0/blob/449f84ea78f707c273e316bcebbfd13e400e57/hardware/CATALYST%20V2.0%20Pinout.png</a> <a href="https://github.com/FYSETC/Catalyst_Kit_V2.0/blob/449f84ea78f707c273e316bcebbfd13e400e57/hardware/CATALYST%20V2.0%20E4%B0%8D%E5%8F%B7%E5%98%BE.pdf">https://github.com/FYSETC/Catalyst_Kit_V2.0/blob/449f84ea78f707c273e316bcebbfd13e400e57/hardware/CATALYST%20V2.0%20E4%B0%8D%E5%8F%B7%E5%98%BE.pdf</a>	<a href="https://github.com/FYSETC/FYSETC_Bullant_V1.0/blob/90d78536b823cc0e31b075f60f8d90145677ea5/Bullant%20V1.0%20PINOUT.pdf">https://github.com/FYSETC/FYSETC_Bullant_V1.0/blob/90d78536b823cc0e31b075f60f8d90145677ea5/Bullant%20V1.0%20PINOUT.pdf</a>
<b>CPU / RAM</b> CM68 core based on RK3568 Quad Core 2GB Ram möglicherweise CM4 kompatibel ??	Allwinner R329 Dual-Core Cortex-A53 ARM CPU_Sip 256MB DRAM
<b>eMMC Storage</b> 32GB	-
<b>Network</b> 1Gb Kein Autonegotiation auf 100mBit	100mBit
<b>WLAN / Bluetooth</b> WLAN, Bluetooth	-
<b>USB</b> 2x USB3.0	1x USB2.0
<b>µController</b> STM32F446	RP2040
<b>Treiber</b> TMC2209	TMC2209 + GC6609
<b>RGB</b> vorhanden	vorhanden
<b>Fans</b> 3x geregelt bis 24V	1 Fan
<b>Temp</b> 3x Temp	1x Temp
<b>CAN Bus</b> vorhanden	-
<b>Sonstiges</b> I2C, SPI, extra 2x UART	-

## Besonderheiten

- **M36 Boards nicht Pinkompatibel** (Anschluss)
  - anderes Pinout am Stecker aber gleiche Stecker / Buchse
- M36 Boards sehen auch identisch aus
- [https://github.com/FYSETC/M36\\_HUB\\_V1](https://github.com/FYSETC/M36_HUB_V1)
- keine root Partition mit armbian Konfig
- Image für Catalyst laut Pi Imager defekt weil Bytesumme nicht durch 512 teilbar
- Catalyst Board geht bei 100MBit Netzwerk nicht Online!!
- Zugriff auf Bullant per seriellem Port (für Init) → unpraktisch
- Bullant macht direkt Update nach Erststart → CPU geblockt
- installiertes octoeverywhere → Remote Access
- Update CM68
  - plugin the USB3.0 A-A cable into the interface on the upper layer of the blue USB3.0 socket,
  - open the “RKDevTool\_Release”,
  - hold the recovery button, click the reset button, when the RKDevTool found device, release the 2 buttons
  - Click the Upgrade Firmware tab, click the Firmware button to select the firmware, and click the Upgrade button to upgrade
  - Wait for the upgrade to complete. Remember not to cut off the power or unplug the data cable during the process, otherwise the upgrade will fail or even damage the CM68.

## Linux Lookaround

- `sudo apt update && sudo apt upgrade -y && sudo apt install -y git silversearcher-ag wavemon hexedit sudo tcpdump iptraf mc htop dcfldd nano usbutils ranger tldr ncd u can-utils multtail fd-find lsof xllvnc terminator minicom cutecom joystick jstest-gtk && mkdir -p ~/.local/share && tldr -u`
- `cat /etc/os-version, lsb_release -a`
- `uname -a`
- `free, htop` → Systemauslastung
- `df -h`

## Doom compilieren (chocolate)

- basierend auf [https://www.chocolate-doom.org/wiki/index.php/Building\\_Chocolate\\_Doom\\_on\\_Debian](https://www.chocolate-doom.org/wiki/index.php/Building_Chocolate_Doom_on_Debian)
- `sudo apt install -y gcc make libsdl2-dev libsdl2-net-dev libsdl2-mixer-dev automake autoconf libtool git pkg-config`
- `git clone https://github.com/chocolate-doom/chocolate-doom.git`
- `cd chocolate-doom && ./autogen.sh`
- `make -j4`
- `sudo make install`

From:

<https://www.drklipper.de/> - Dr. Klipper Wiki

Permanent link:

[https://www.drklipper.de/doku.php?id=klipper\\_faq:sbcs:fysetc\\_catalyst\\_bullant&rev=1715700856](https://www.drklipper.de/doku.php?id=klipper_faq:sbcs:fysetc_catalyst_bullant&rev=1715700856)

Last update: **2024/05/14 17:34**

